

Handheld Pulse Oximeter

Model: SA300

WORLD'S FIRST
CHECK OF
ARTERY CONDITION
WITH SpO2 & PULSE RATE
PULSE OXIMETER



- Artery Check Technology (ACT) embedded
- Instant readings of SpO2, Pulse Rate and artery condition in 1 minute
- Big 2.4" color TFT display
- Personal SpO2, Pulse Rate, Memory Interval thresholds setting
- Shielded Design blocks Ambient Light
- Biocompatibility & Anti-Allergic Design
- Alert function
Device delivers audible warning when measurement result exceeds the SpO2/Pulse Rate thresholds previously set.
- Silent mode Disables the beep sound during the measurement by pressing the "Sound" button.
- Up to 999 Memories
Could be programmed with 3 intervals: 10 / 30 / 60 seconds
- Bluetooth® Transmission
- Pulse Strength Indicator
- Dual power source
- Protection pouch



Artery Check Technology



%SpO2 & Pulse Rate




2.4" Color Display



High/Low SpO2, PR & Memory Interval Setting



Shielded Design blocks Ambient Light



Biocompatibility & Anti-Allergic Design



Alert & Sound Off



Up to 999 memories



Pulse Strength Indication



PPG/ACT Waveform



Battery and AC Adaptor



Protection Pouch



Bluetooth® Transmission

The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Rossmax International Ltd. is under license. Other trademarks and trade names are those of their respective owners.

ACT (Artery Check Technology)

ACT (Artery Check Technology) analysis the pulse and SpO2 signals and determines the actually prevailing stiffness of the artery (Artery Condition). ACT further comprehensively classifies the arterial condition into 6 levels and presents the result by an intuitive graphical visualisation. Pulse rate, SpO2 and the artery condition are available at your fingertip!

Pulse Oximeters with ACT detects

- Artery Condition
- SpO2
- Pulse Rate



Specification

Measurement Range | SpO2: 35%~100%; PR: 30~250 bpm **Precision** | SpO2: 70%~100%; ±2%; 35%~69% (unspecified); Pulse rate: 30~250bpm; ±3
SpO2 Accessory | Adult Probe Included, Pediatric / Neonatal Probe Optional
Power Supply | 4 x "AA" Alkaline / AC Adaptor

Model	Qty per carton	Carton volume
SA300	10 pcs	0.055 cbm/ctn

Storage temperature: -25°C - 70°C (-13°F - 158°F)
 Relative humidity: 15% - 90% (no condensing)
 Atmospheric Pressure: 700 to 1060 hPa

Distributed by:

CONSTAR X PTY LTD

Unit 4, 68 Parramatta Road, Underwood, QLD 4119,
 Australia. Ph: 1300 778 924

www.constar.com.au